

LH104 SWIVEL



STANDARD SWIVEL

CATALOG NUMBER	MINIMUM BREAKING STRENGTH-LBS.	OUTSIDE DIAMETER	PIN SIZE	CLEVIS WIDTH	LENGTH OVERALL
LH104-35	35,000	1-1/4"	1/2"	9/16"	5"
LH104-75	75,000	1-3/4"	5/8"	3/4"	6"
LH104-150	150,000	2-3/8"	7/8"	1"	8.25"

MORPAC INDUSTRIES, INC.

39

117 Frontage Road North, Suite A
Pacific, WA 98047-1052

Website: <http://www.morpac.com/>
Email: actuators@morpac.com

Phone:(253) 735-8922
Fax: (253) 735-8933

LH104 SWIVEL

- Swivels available in standard (previous page) or torpedo (below) configuration
- High strength heat treated aircraft stainless steel, with thrust needle bearing and Teflon type bushing for high corrosion resistance, long life and to eliminate brinelling.
- All swivel pins are of the screw type with an Allen wrench insert
- Replacement or extra pins and Allen wrenches are available. Specify swivel catalog number.
- Swivels have minimum breaking strength on the order of two times as great as conventional alloy steel swivels
- Rubber cone and threaded sleeves sold separately.



TORPEDO SWIVEL (shown with LH58 Leadcone)

CATALOG NUMBER	MINIMUM BREAKING STRENGTH-LBS.	OUTSIDE DIAMETER	PIN SIZE	CLEVIS WIDTH	LENGTH OVERALL
LH104-100T	100,000	2-1/16"	3/4"	3/4"	7.6"
LH104-150T	150,000	2-3/8"	7/8"	1"	8.25"

MORPAC INDUSTRIES, INC.

40

117 Frontage Road North, Suite A
Pacific, WA 98047-1052

Website: <http://www.morpac.com/>
Email: actuators@morpac.com

Phone:(253) 735-8922
Fax: (253) 735-8933